



Portable Generators

TSURUMI PUMP x POWERED by HONDA

TPG
60Hz



- **TSURUMI TPG-series portable generators** are designed to withstand the severe conditions of construction jobsites or industrial applications, especially where extra durability and dependable, stable power are required. Ideal to supply the power to Tsurumi's single-phase submersible pumps and all your electrical power tools such as drills, saws, lighting and heaters due to AVR system.
- **Powered by Honda OHV engine** for efficient fuel and oil consumption with oil alert system to shut off motor if oil falls below safe operation level.
- Large Air Filter for superior emission control.
- Large, Silent Muffler to greatly reduce noise.
- Rubber Vibration Pads isolate generator/engine set for maximum protection and noise reduction.
- High Capacity Fuel Tank with Fuel Gauge for extended run-time.
- Volt Meter, Pilot Lamp and DC 12V Outlet are equipped as standard.
- Electric Starter makes free from extra work for start-up.

Standard Accessories

- NEMA 5-15P Plug×2
- NEMA L14-30P Twist Lock Plug×1
- NEMA L5-30P Twist Lock Plug×1 (TPG-7000HM/HEL only)
- DC 12V Plug w/Cord & Clip×1
- Hexagon Wrench

Model Selection 60Hz



Electric Starter available for TPG-7000HEL only



Wheel kit available as option

Model	TPG-3000HM	TPG-7000HM	TPG-7000HEL		
Engine	Engine Brand			HONDA	
	Engine Model		GX160	GX390	
	Displacement (cm ³ / cu.in.)		163 / 9.95	389 / 23.75	
	Max. Output (kW / 4000min ⁻¹)		4.0	9.6	
	Type				Air Cooled, 4-cycle, OHV Gasoline Engine
	Oil Alert System				Standard
	Ignition System				Transistor (C.D.I.)
	Starting System		Recoil Starter	Electric Starter	
Generator	Alternator			Self-exciting, 2-pole, Field Rotating Type, Single-phase	
	Voltage Regulator			AVR	
	Phase			Single	
	AC Max. Output (kVA)		2.8	7.2	
	AC Rated Output (kVA)		2.4	6.1	
	Rated Voltage				110/220V (Dual)
	AC Outlet		125V-20A Duplex Receptacle×1 125/250V-30A Twist Lock Receptacle×1	125V-20A Duplex Receptacle×1 125/250V-30A Twist Lock Receptacle×1 125V-30A Twist Lock Receptacle×1	
DC Outlet				12V-8.3A Receptacle×1	
Other Features	Pilot Lamp			Standard	
	Volt Meter			Standard	
	Fuel Tank Capacity (L / USG)		16 / 4.22	25 / 6.6	
	Continuous Operating Hours (hr: 100% Load)		12.1	7.6	
	Sound Level (dbA / 7m)		75	79	
Measurement	Dimensions L×W×H (mm / in.)		601×420×501 / 23.7×16.6×19.8	691×541×515 / 27.3×21.3×20.3	
	Dry Weight (kg / lb)		46 / 101.4	82 / 178.1	85 / 184.6

We reserve the right to change the specifications and designs for improvement without prior notice.

TSURUMI MANUFACTURING CO., LTD.

Your Dealer